



ISDN PCMCIA CARD



DTA-128+

This PCMCIA card serves as an ISDN terminal adapter (TA) for your notebook PC. It plugs into a PCMCIA slot of your notebook to connect it to an ISDN line to send data, faxes and logon to the Internet.

The card provides an S/T Basic Rate Interface (BRI) total 128Kbps, which includes 2 B channels for data transmission and 1 D channel for signal transmission. Each B channel can be used separately to connect to 2 different destinations, or combined together to double the bandwidth in a load-sharing mode.

G3 and G4 faxes are supported. Fax software is included.

KEY FEATURES

- 128Kbps ISDN PC card
- G3 fax connection over ISDN B channel
- Menu-driven configuration utility provided
- Runs Windows Hyperterm, Procom Plus

TECHNICAL INFORMATION

- PCMCIA standard: 2.x, PC Card 95, JEIDA 4.x Type II
- EMI: CE Class B
- Telecom certification: FCC, Japan JATE, Germany Reg TP ICT (D810083L), CTR3 (CE 0682X)

ISDN

- Interface: S/T Basic Rate Interface
- D channel: DSS1 (Euro-ISDN), NI-1, INS-Net 64
- B channels: V.120, V.110, PPP/MP, Async-to-Sync PPP conversion, HDLC raw data
- Application program interfaces: AT Command (VCOMM), Win ISDN, NDIS, CAPI 2.0, NAF ISDN PCI
- G3 faxing (over B channel): CAPI mode
- Telephony (over B channel): CAPI mode

ISDN Network & Switch Compatibility

- National ISDN-1 (NI1)
- AT&T 5ESS Custom
- Northern Telecom DMS-100 Custom
- DSS1 (Euro-ISDN)
- INS-Net 64

Drivers

- Microsoft Windows 95, 95 OSR2, 98, 2000, NT 4.0, XP

ORDERING INFORMATION

ISDN PCMCIA Card

DTA-128+ RJ-45 plug for ISDN line (S/T Interface)

* S/T interface requires an external NT-1 device
This product currently supports European countries only